

Featuring 65'+ peak and camber glulam beams, this pickleball open court not only provides a more aesthetically appealing venue than other build options, but also improves sound quality on the courts compared to what steel structures would offer.

- 65' x 68'
- Open-air dual pickleball courts
- Four 65'+ beams

Spearheaded by Western Wood Structures, the Black Diamond Pickleball Court presented a unique challenge to create an open-air shelter that would accommodate two courts, allowing residents to enjoy year-round play despite the region's notorious Northwest rain.

The primary challenge of the project lay in creating an effective shelter that not only protected players from the elements but also maintained an open-air feel, in harmony with the surroundings.

WWS envisioned a structure with 4' overhangs, which was made possible by the use of dapped Peak and Camber Beams designed to receive the purlins.

"We value quality and timing.

Zip-O also has a wide range of capabilities for tackling unique jobs and the service can't be beat."

- Dan Herr, WWS



The Black Diamond Pickleball Court boasts four Large Peak and Camber Glulam Beams, each playing a crucial role in the structural integrity and visual impact of the shelter.

Manufactured by Zipo in Eugene, Oregon, these beams exemplify precision engineering and superior craftsmanship.

DESIGN CHALLENGES

The primary challenge of the project lay in creating an effective shelter that not only protected players from the elements but also maintained an open-air feel, in harmony with the surroundings.

WWS envisioned a structure with 4' overhangs, which was made possible by the use of dapped Peak and Camber Beams designed to receive the purlins.



BEAM SPECS

Dimensions of the 2 Larger Beams:

- Width: 8-3/4"
- Depth: Tapering from 20" on the ends to just over 74" deep in the middle
- Reinforcement: Secured with 16 lag screws for radial reinforcement.

Dimensions of the 2 Smaller Beams: Width:

- 8-3/4" Depth: Tapering from 11" at the ends to just over 64" deep in the middle
- Reinforcement: Lag screws utilized for radial reinforcement, ensuring structural stability

